



The SH-LPM is a wide dispersion fully horn-loaded monitor loudspeaker. Due to the large horn mouth the SH-LPM offers substantial directivity with front to back rejection and high gain before feedback. High frequencies are very smooth throughout the coverage pattern and are not beamy. Applications include anywhere wide coverage with high directivity is desired. With its combination of performance, clarity, low profile aesthetics and waterproof grill the SH-LPM sets a new benchmark in floor monitor loudspeakers.

Specifications

- Coverage Pattern 110° conical
- Operating Frequency Range..... 60 Hz - 20 kHz +/- 3 dB
..... 52 Hz – 24 kHz -10 dB
- Sensitivity @ 1M 95 dB SPL
..... (Measured as 2.83V input, 1M half space)
- Maximum Output 120 dB SPL Cont., 126 dB SPL Program
- Input Power Ratings 300W continuous, 600W program
- Nominal Impedance 8 ohms
- Minimum Impedance 6 ohms @ 8 kHz
- Recommended Processing..... 60 Hz HP @ 24 dB/Butterworth
- Drivers Single 8” coaxial
- Input Connections..... 4-NL4MP (2 per side)
- Enclosure Material 13ply, 18mm Baltic Birch, polyurea coated

SH-LPM

Stylish Low-Profile Monitor with inputs on both sides



Accessories

Weatherized options available

PERFORMANCE DATA

Model	Max SPL	Sensitivity	Magnitude Response	Beam Width	Power Rating	Dimensions (in.)	Weight
SH LPM	126 dB	95 dB	60 Hz – 20 kHz	110° conical	600 W	13.6 x 21.5 x 18	41 lbs