

LOUDSPEAKER

AMPLIFIER

SH25 -----	Three Channel-1000-500-500
SH46 -----	Three Channel-1000-500-500
SH50 -----	Three Channel-1000-500-500
SH60 -----	Three Channel-1000-500-500
SH64 -----	Three Channel-1000-500-500
SH69 -----	Three Channel-1000-500-500
SH95 -----	Two Channel-500-250
SH95HO -----	Two Channel-500-250
SH96 -----	Three Channel-1000-500-500
SH96HO -----	Single Channel-1000 - Mid/High Single Channel-4000 - Low
SM60MH -----	Single Channel-2500
SM60F-----	Single Channel-1000
SM96 -----	Single Channel-1000
SM100-----	Two Channel-200-200
SM100CIN-----	Two Channel-200-200
SM100B -----	Three Channel-1000-500-500
SM100F -----	Three Channel-1000-500-500
GH60-----	Three Channel-1000-500-500
GH40-----	Three Channel-1000-500-500
SBH-10-----	Single Channel-2400
SBH-20LF-----	Single Channel-1000
TH112-----	Single Channel-1000
TH115-----	Single Channel-1000
TH118-----	Single Channel-2400
TH212-----	Single Channel-2400
TH412-----	Single Channel-4000
TH221-----	Single Channel-4000
TH812-----	Single Channel-4000 qty 2
BC-412 -----	Single Channel-4000
BC-415 -----	Single Channel-4000 qty 2
DBH218-----	Single Channel-4000
DBH218LC -----	Single Channel-4000
DTS20-----	Single Channel-1000
DTS10-----	Single Channel-1000
THSPUD-----	Single Channel-1000
CS30-----	Single Channel-1000

SPECIFICATIONS

Frequency response: 20-20KHz +/- 1 dB
 THD+N: 0.02% typical
 Sensitivity: +4dBV
 Input Impedance: 35K ohm
 CMRR : >90dB
 Damping factor: >200
 Signal to noise: -95dB 20-20KHz ref full output
 Latency: 460 microseconds standard DSP.
 1.2 milliseconds Cobramote DSP
 AC mains: 90-132VAC, 55-65Hz or
 190-.265VAC, 45-55Hz switchable

Single Channel-1000

1000W/4 ohms 500W/8 ohms
 Power consumption:
 AC draw at 1/8th max output - 180W / at idle - 17W
 Size and weight: 7 x 15.7 x 2.8 in 7lbs

Single Channel-2400

2400W/4 ohms 1300W/8 ohms
 Power consumption:
 AC draw at 1/8th max output - 345W / at idle - 18W
 Size and weight: 7 x 15.7 x 2.8" 7lbs

Single Channel-4000

4000W/2 ohms 2400W/4 ohms 1300W/8 ohms
 Power consumption:
 AC draw at 1/8th max output - 585W / at idle - 20W
 Size and weight: 7 x 15.7 x 2.8 in 7lbs

Two Channel-200-200

LF: 200W/4 ohms 110W/8 ohms
 HF: 200W/4 ohms 110W/8 ohms
 Total supply power 260W
 Power consumption:
 AC draw at 1/8th max output - 70W / at idle - 12W
 Size and weight: 5.3 x 10.3 x 2.8" 2.5lbs
 7 x 15.7 x 2.8" 5lbs

Two Channel-500-250

LF: 500W/4 ohms 250W/8 ohms
 HF: 250W/4 ohms 125W/8 ohms
 Total supply power 625W
 Power consumption:
 AC draw at 1/8th max output - 160W / at idle - 18W
 Size and weight: 7 x 15.7 x 2.8" 6lbs

Three Channel-1000-500-500

LF:1000W/4 ohms 500W/8 ohms
 MF: 500W/4 ohms 250W/8 ohms
 HF: 500W/4 ohms 250W/8 ohms
 Total supply power 1250W
 Power consumption:
 AC draw at 1/8th max output - 320W / at idle - 25W
 Size and weight: 7 x 19.3 x 2.8" 10lbs