

The SH50 works anywhere great fidelity; low frequency pattern control and unrivaled Magnitude/phase response are required. It has the added benefit of truly modular array-ability. For high SPL and low distortion sound reproduction.

Available in both Touring and Install versions - touring version comes with handles to make it easily transportable.

Specifications

Coverage Pattern	50° horizontal x 50° vertical
	50 Hz - 18 kHz +/- 3 dB
	100 dBSPL
	(Measured as 2.83V input, 1M whole space)
Maximum Output	127 dBSPL Cont.,133 dBSPL Peak
Input Power Ratings	1000W continuous, 4000W Peak
Nominal Impedance	4 ohms
Minimum Impedance	3.5 ohms @ 1 kHz
Recommended Processing	40 Hz HP @ 24 dB/Butterworth
Drivers	LF 2 x 12", MF 4 x 5" HF 1 x 1"
Input Connections	2-NL4MP
Enclosure Material1	3ply, 18mm Baltic Birch, polyurea coated





SH50 The Flagship of the Synergy Horn Line



Accessories

Powered version available Mounting brackets for array MB 50 Fly-ware 50-OFW Outer Fly-ware Speaker Cover Weatherized options available

PERFORMANCE DATA

Model	Max	Sensitivity	Magnitude	Beam Width	Power	Dimensions (in.)	Weight	
	SPL		Response		Rating			
SH50	133 dB	100 dB	50 Hz – 18 kHz	50° x 50°	2,000 W	28 x 28 x 25.5	133 lbs	

© 2012 Danley Sound Labs. All Rights Reserved.

www.danleysoundlabs.com

Architect/Engineers Specs

The loudspeaker shall utilize the synergy Horn/Tapped Horn patent-pending enclosure covering three pass bands. The coverage pattern shall be 50° horizontal x 50° vertical. The loudspeaker shall have an operating rage of +/- 3 dB 50 Hz – 18 kHz. Sensitivity of 100 dBSPL @ 1m. Output of 127 dBSPL/133 dBSPL Peak. Power handling shall be 1000 Watts continuous, 2000 Watts peak. The impedance shall be nominal 4 ohms.

The loudspeaker shall be constructed of 13 ply Baltic birch, water resistant Polyurea coated, properly braced for the intended use and a rugged steel grill. The connectors shall be Neutrik NL4. The Loudspeaker shall be the Danley Sound Labs SH50.