

Thank you for purchasing the OS80 Pole Mount Kit. The kit should include the following:

- 2 x Pole Mount Stainless Steel Banding
- 2 x BCLAMP Banding Tensioner
- 1 x PM-G-6+ Mounting Arm
- 1 x 1/2" by 3" Long Bolt
- 2 x 1/2" Washer
- 1 x 1/2" Lock Washer

PMK2 (Additional items)

- 1 x CB-G-48 Extension Arm
- 2 x 1/2" by 3" Long Bolt
- 1 x 1/2" by 5.5" Long Bolt
- 3 x 1/2" Lock Washer
- 6 x 1/2" Washer

Compatible Pole Dimensions

Max: 24" Diameter

Custom Order required for longer strap lengths.

Min: 8" Diameter

It is highly recommended that a licensed engineer approves use of this product.


Weight

PMK-1: 66 lbs 30 kgs

PMK-2: 126 lbs 58 kgs

Below are illustrations of how the bracket attaches to the u-bracket and light pole. The purpose of the kit is to add an adjustable mounting bracket to your loudspeaker and connect it to a standard light pole.

- Slide the steel banding through the slots on the mounting arm, and around the pole.
- Attach the bclamps to the ends of the banding, fold the slack under the clamps (figure 1), and connect the two ends with the 6" bolt and tighten.
- To attach the speaker to the bracket place a bolt with washer through the top of the mounting arm.
- Lift the OS80 and slide the bolt through the u-bracket on the speaker.
- Pull the backstrap on the OS80 into place and over the bolt.
- Place a washer, lock washer, and nut on the bolt and tighten.



(figure 1)

